



BUSSMANN STANDARD PANEL MOUNT FUSE HOLDERS
 Straight Solder Terminals E14853 47235

STOCK NO.	Fig.	Mounting Position/Type	Fuse Size (In.)	Rating	Profile	Price Each			
						1	100	500	1000
HJM	A	Front / Hex nut	1/4x1	5A @ 125V	Low	CALL	for	Prices	
HKP	A	Front / Hex nut	1/4x1 1/4	30A @ 250V	Low				
HKP-CC	A	Front / Hex nut	1/4x1 1/4	30A @ 250V	High				

FUSE HOLDERS AND CLIPS
 PCB Fuse Holders • "Kicked" terminals for optimum wave soldering • Anti-wicking terminals E14853 47235

STOCK NO.	Fig.	Fuse Size	Rated To		Price Each			
			Amp	Volt	1	50	100	500
HBH-I	I	1/4" x 1-1/4"	12	250	Call	For	Prices	
HBV-I	J	1/4" x 1-1/4"	12	250				
HBH-M	I	5mm x 20mm	12	250				
HBV-M	J	5mm x 20mm	12	250				

PANEL MOUNT FUSE HOLDERS

- Flammability rating: UL 94V-0
- Terminal type: 3/16" solder/quick connect
- Temperature range: -55°C to 85°C
- Current rating: UL - 15A @ 250V VDE - 10A @ 250V
- CSA - 16A @ 250V
- SEMKO - 10A @ 250V

Standard (for 1/4" x 1 1/4" Fuses)

STOCK NO.	Fig.	Mounting Position/Type	Profile	Fuse Access	Rear Terminal	Price Each			
						1	100	500	1000
HTB-22I	B	Rear Hex Nut	Low	Knob	Straight	Call	For	Prices	
HTB-24I	B	Rear Hex Nut	Low	Knob	Rt.Angle				
HTB-26I	B	Rear Hex Nut	Low	Knob	Straight				
HTB-28I	B	Rear Hex Nut	Low	Knob	Rt.Angle				
HTB-32I	C	Rear Hex Nut	Low	Slotted	Straight				
HTB-34I	C	Rear Hex Nut	Low	Slotted	Rt.Angle				
HTB-36I	C	Rear Hex Nut	Low	Slotted	Straight				
HTB-42I	D	Rear Hex Nut	High	Knob	Straight				
HTB-44I	D	Rear Hex Nut	High	Knob	Rt.Angle				
HTB-46I	D	Rear Hex Nut	High	Knob	Straight				
HTB-48I	D	Rear Hex Nut	High	Knob	Rt.Angle				
HTB-54I	E	Rear Hex Nut	High	Slotted	Rt.Angle				
HTB-56I	E	Rear Hex Nut	High	Slotted	Straight				
HTB-58I	E	Rear Hex Nut	High	Slotted	Rt.Angle				
HTB-62I	F	Front Hex Nut	High	Knob	Straight				
HTB-64I	F	Front Hex Nut	High	Knob	Rt.Angle				
HTB-66I	F	Front Hex Nut	High	Knob	Straight				
HTB-82I	G	Front Snap-In	Low	Knob	Straight				
HTB-86I	G	Front Snap-In	Low	Knob	Straight				
HTB-88I	G	Front Snap-In	Low	Knob	Rt.Angle				
HTB-92I	H	Front Snap-In	Low	Slotted	Straight				
HTB-98I	H	Front Snap-In	Low	Slotted	Rt.Angle				

Miniature (for 5mm x 20mm Fuses)

STOCK NO.	Fig.	Mounting Position/Type	Profile	Fuse Access	Rear Terminal	Price Each			
						1	100	500	1000
HTB-26M	B	Rear Hex Nut	Low	Knob	Straight	Call	for	prices	
HTB-28M	B	Rear Hex Nut	Low	Knob	Rt.Angle				
HTB-32M	C	Rear Hex Nut	Low	Slotted	Straight				
HTB-36M	C	Rear Hex Nut	Low	Slotted	Straight				
HTB-38M	C	Rear Hex Nut	Low	Slotted	Rt.Angle				
HTB-42M	D	Rear Hex Nut	High	Knob	Straight				
HTB-46M	D	Rear Hex Nut	High	Knob	Straight				
HTB-56M	E	Rear Hex Nut	High	Slotted	Straight				
HTB-62M	F	Front Hex Nut	High	Knob	Straight				
HTB-82M	G	Front Snap-In	Low	Knob	Straight				
HTB-92M	H	Front Snap-In	Low	Slotted	Straight				

In-Line Fuse Holders

* Leads not supplied

STOCK NO.	Fig.	Fuse Size	Lead Lth. (In.)	Price Each			
				1	50	100	500
HRK	K	Accepts all 1/4" fuses,	8	Call	For	Prices	
HMJ	K	5/8" through 1 1/4" long	8				
HFB	L	1/4 X 1 1/4" waterproof	---				

Fuse Blocks

- 1/4" x 1 1/4" fuse size
- Spring-bronze clips
- Anti-pivot barrier
- Totally sealed base

STOCK NO.	Fig.	Description	Rated To		Price Each			
			Amp	Volt	1	50	100	500
S-8001-1	M	Solder terminal	25	300	Call	For	prices	
S-8101-1	M	3/16" quick connect	15	300				

FUSE CLIPS AND BLOCKS

Twin Clips

Makes it unnecessary to replace blown pigtail fuse by cutting or soldering. Twin-clips snap on the blown fuse.

STOCK NO.	Fig.	Fuse Size	Price Each			
			1	50	100	500
3434	N	5/8" to 1 1/4" long; insulated				

Fuse Clips

- Made of spring bronze

STOCK NO.	Fig.	Description	Rated To		Price Each			
			Amp	Volt	1	50	100	500
5678-14	O	1/4" solder terminal	Call			for	prices	
5682-41	P	1/4" screw mount						
1A1119-10	Q	1/4" PC mount with stop						
1A1120-10	R	1/4" PC mount						
1A3399-10	S	5mm PC mount with stop						

- Molded bakelite base
- Silver plated clips
- Beryllium copper solder terminal

STOCK NO.	Fig.	Description	Rated To		Price Each			
			Amp	Volt	1	50	100	500
3828-1	T	1" fuse size	30	250	Call	for	prices	
4405	U	1 1/4" fuse size	30	250				
4408	V	1 1/4" fuse size	30	250				